



				FINI	SH SCHE	DULE								D	OOR SCH	EDULE					
ROOM FINISHES					DOOR	LEAF	DOOR	D	DOOR SIZE			FIRE		DETAILS		HARD-					
					WAI	NSCOT	CEILING		NO.	COUNT	TYPE		HEIGHT 1	HICK.	FRAME		. HEAD	JAMB	SILL	WARE	
NO.	NAME	FLOOR	BASE	WALL	FINISH	HEIGHT	FINISH HEIGH	T REMARKS	100	2	MG3	3' - 0"	7' - 7 1/2"	1 3/4"	HMA		4/40.0	0/40.0	6/A3.3	1	
						1			<u> </u>	1	WG2 WF	3' - 0" 3' - 0"	7' - 0" 7' - 0"	<u>1 3/4"</u> 1 3/4"	HMA HMA		1/A3.2 1/A3.2	3/A3.2 3/A3.2	12/A3.3 9/A3.3	14	
100	ENTRY	WD	WD	GYP,WP	WD	5'-0"	WD AGT OV/D	1	102	1	WF	3' - 0"	7' - 0"	1 3/4"	HMA		1/A3.2	3/A3.2	9/A3.3	15	
101	RECEPTION	<u> </u>	R	GYP		5'-0"	ACT,GYP	1	104	1	WNF	3' - 0"	7' - 0"	1 3/4"	HMA		1/A3.2	3/A3.2	20/A3.3	16	
102	OFFICE	C	R	GYP		5'-0"	ACT	1,2	105	1	WF	3' - 0"	7' - 0"	1 3/4"	HMA		1/A3.2	3/A3.2	12/A3.3	13	
103	OFFICE	С	R	GYP		5'-0"	ACT	1,2	105.1	1	WF	3' - 0"	7' - 0"	1 3/4"	HMA		1/A3.2	3/A3.2	9.A3.3	13	
104	WORK CONFERENCE	LVT WD	R WD	GYP GYP,WP		5'-0"	ACT ACT,GYP		107	2	MG3	3' - 0"	7' - 7 1/2"	1 3/4"	HMA				6/A3.3		
105	CORRIDOR	WD	WD	GYP,WP GYP,WP		5'-0"	ACT,GYP	1,2	107.1	2	WNF	3' - 0"	7' - 0"	1 3/4"	HMA	90 MIN	1/A3.2	3/A3.2	12/A3.3	3	
100	WEST STAIR	C	R	GTF,WF GYP		5-0	ACT	1,10	108	1	WF	3' - 0"	7' - 0"	1 3/4"	HMA		1/A3.2	3/A3.2	30/A3.3	9	
107	WOMEN'S	CT	CT	CT, GYP	СТ	7'-0"	ACT	1,2,5,6	109	2	WF	3' - 0"	7' - 0"	1 3/4"	HMA		1/A3.2	3/A3.2	25/A3.3	4	
100	CORRIDOR	LVT	R	GYP	01	1-0	ACT	1,5,6,11	109.1	2	MF	3' - 0"	7' - 0"	1 3/4"	T(AMA)	90 MIN	1/A3.2	3/A3.2	24/A3.3		
110	VEST	LVT	R	GYP			ACT	1	110	1	WF	3' - 0"	7' - 0"	1 3/4"	HMA		1/A3.2	3/A3.2	24/A3.3	13	
111	TOILET	LVT	R	CT, GYP	СТ	7'-0"	ACT	1,2,5,6	111	1	WF	3' - 0"	7' - 0"	1 3/4"	HMA		1/A3.2	3/A3.2	3/A3.3	12	
112	GREEN ROOM	C	R	GYP			ACT	1	112	1	WF	3' - 0"	7' - 0"	1 3/4"	HMA		1/A3.2	3/A3.2	20/A3.3	13	
113	STAGE	SWF	R,WD	EPCB,GYP,	WD	VARIES	GYP	1	112.1	1	WF	3' - 0"	7' - 0"	1 3/4"	HMA		1/A3.2	3/A3.2	20/A3.3	11	
			,	WP					113.1	1	MF	3' - 0"	7' - 0"	1 3/4"	HMA	45 MIN	1/A3.2	3/A3.2		18	
114	SEATING	C,CONC	WD	GYP,WP	WD	VARIES	ACT,GYP	1	113.2	1	MF	3' - 0"	7' - 0"	1 3/4"	HMA	45 MIN	1/A3.2	3/A3.2	25/A3.3	18	
115	PRE LOBBY	С	WD	GYP,WP	WD	5'-0"	ACT	1	114		WF	3' - 0"	7' - 0"	1 3/4"	HMA	45 MIN	1/A3.2	3/A3.2		18	
117	LOBBY	С		GYP,WP	WD	5'-0"	WD	1	115	1	MF	3' - 0"	7' - 0"	1 3/4"			4/40.0	8/A11.0		8	
118	MEN'S	СТ	СТ	CT, GYP	СТ	7'-0"	ACT	1,2,5,6	115.1	2	WF	3' - 0"	7' - 0"	1 3/4"	HMA	45 MIN	1/A3.2	3/A3.2	9/A3.3		
119	EAST STAIR	С	R	GYP			ACT	1,10		2	WF WF	3' - 0" 3' - 0"	7' - 0" 7' - 0"	<u>1 3/4"</u> 1 3/4"	HMA		1/A3.2	3/A3.2	12/A3.3		
120	MUSEUM	WD	WD	GYP,WP	WD	5'-0"	WD	1	117.1		MF	3 - 0	7 - 0		HMA	45 MIN 45 MIN	1/A3.2	3/A3.2	9/A3.3 2/A3.3		
	ELEV.	-	-	-	-	-	-	1	117.2	1	WF	3' - 0"	7 - 0	1 3/4	/1(HMA) HMA	43 101111	1/A3.2	3/A3.2		9	
122	CORRIDOR		R	GYP	07		ACT	1	119	2	MG3	3' - 0"	7 - 0	1 3/4	HMA		1/AJ.Z	J/AJ.Z	6/A3.3		
	TOILET		R	CT, GYP	CT	7'-0"	ACT	1,5,6	119.1	2	WNF	3' - 0"	7' - 0"	1 3/4"	HMA	90 MIN	1/A3.2	3/A3.2		3	
136	TOILET		R	CT, GYP	CT	7'-0"	ACT	1,5,6	120	1	WG2	3' - 0"	7' - 0"	1 3/4"	HMA	00 10111	1/A3.2	3/A3.2		10	
138	WORK/STOR		R	GYP			ACT	1	120.1	2	WG2	3' - 0"	7' - 0"	1 3/4"	HMA		1/A3.2	_		4	
139	SUPPLY SPRINKLER RISER		R	GYP			ACT	1	122	2	MG1	3' - 0"	7' - 0"	1 3/4"	HMB		1/A3.2	3/A3.2		1	, ,
140			R	GYP			GYP ACT	1	123.1	1	WNF	3' - 0"	7' - 0"	1 3/4"	HMA		1/A3.2	3/A3.2		1	<u></u>
141			R	GYP GYP			AUT	1	126	1	WF	3' - 0"	7' - 0"	1 3/4"	HMA		1/A3.2	3/A3.2		1	<u>,</u>
142 143	MECH EXIST. BASEMENT	LVT	R					1	129	1	WF	3' - 0"	7' - 0"	1 3/4"	HMA		1/A3.2	3/A3.2		8	,
200	COMMON AREA	- WD	- WD	- GYP	WD	5'-0"	- ACT	1,12	131	1	WF	3' - 0"	7' - 0"	1 3/4"	HMA		1/A3.2	3/A3.2		-	-
200	MECH.	LVT	R	GYP		5-0		1	133	1	WF	3' - 0"	7' - 0"	1 3/4"	HMA		1/A3.2	3/A3.2			5
201.1	WEST STAIR	C	R	GYP			ACT	1,10	135	1	WF	3' - 0"	7' - 0"	1 3/4"	HMA		1/A3.2	3/A3.2		12	
200	WOMEN'S	LVT	R	CT, GYP	СТ	7'-0"	ACT	1,2,5,6	136	1	WF	3' - 0"	7' - 0"	1 3/4"	HMA		1/A3.2	3/A3.2	24/A3.3	12	
205	MEN'S	LVT	R	CT, GYP	CT	7'-0"	ACT	1,2,5,6	137	2	WF	3' - 0"	7' - 0"	1 3/4"	HMA						
206	CUST.	LVT	R	CT, GYP	CT	7'-0"	GYP	1,5,6	138	1	MF	3' - 0"	7' - 0"	1 3/4"	HMA		1/A3.2	3/A3.2	20/A3.3	17 1	1
207	SECOND FLOOR SEATING	C	R	GYP,WP	WD	5'-0"	ACT,GYP	1	139	1	WF	3' - 0"	7' - 0"	1 3/4"	HMA 1 (HMB)		1/A3.2	3/A3.2	20/A3.3	17 1	1
208	EAST STAIR	C	R	GYP,WP			ACT	1,10	140	1	MF	3' - 0"	7' - 0"	1 3/4"			1/A3.2	3/A3.2	1/A3.3	2	
211	MECH/DATA	LVT	R	GYP				1	201	1	WF	3' - 0"	7' - 0"	1 3/4"	HMA		1/A3.2	3/A3.2			
212	MECH	LVT	R	GYP				1	201.1	1	MF	3' - 0"	7' - 0"	1 3/4"	HMA		3/A3.5	8/A3.5		19	
214	CORRIDOR	WD	WD	GYP,WP	WD	5'-0"	ACT,GYP	1,5,6,11	202	1	WF	3' - 0"	7' - 0"	1 3/4"	HMA		1/A3.2	3/A3.2			
	·								203	2	WNF	3' - 0"	7' - 0"	1 3/4"	HMA		1/A3.2	3/A3.2			
									204	1	WF	3' - 0"	7' - 0"	1 3/4"	HMA		1/A3.2	3/A3.2		9	
							NOTE:	ROOMS WITH NO WORK ARE NOT SCHE		1	WF	3' - 0"	7' - 0"	1 3/4"	HMA		1/A3.2				
									206		WF	3' - 0"	7' - 0"	1 3/4"	HMA		1/A3.2	3/A3.2			
									207	1	WF	3' - 0"	7' - 0"	1 3/4"	HMA		1/A3.2			18	
									208	2	WNF	3' - 0"	7' - 0"	1 3/4"	HMA		1/A3.2	3/A3.2		3	
									209	1	WF	3' - 0"	7' - 0"	1 3/4"	HMA		1/A3.2			10	—
				SH REN					210 211		WF MF	3' - 0" 3' - 0"	7' - 0" 7' - 0"	<u>1 3/4"</u> 1 3/4"	HMA HMA		1/A3.2 1/A3.2	3/A3.2	26/A3.2	13	
													/ / / / / / / / / / / / / / / / / / / /				1 1/1/1				

		FINISH REMARKS	
1.		E BUILDING SPRINKLER SYSTEM IN ACCORDANCE WITH N.I	=.P.A. 13. LC
2	-	TE IN MANNER TO PREVENT FREEZING. E AND INSTALL SOUND BATTS AT ALL WOOD STUD WALLS '	
2. 3.		E ARCHITECTURAL FLOOR PATTERN UTILIZING (3) COLORS	
	MANUFA	ACTURERS STANDARD COLORS, SEE PLANS FOR FLOOR GR	RAPHICS.
4. 5.	-	E AND INSTALL R-19 BATT INSULATION OVER ENTIRE CEILII E TILE OVER TILE BACKER PANELS WHERE TILE OCCURS.	NG WITHIN T
5. 6.		BEHIND PLUMBING FIXTURES TO RECEIVE TILE.	
7.		TO REFLECTED CEILING PLANS FOR HORIZONTAL LIMITS O	
8. 9.		TO REFLECTED CEILING PLAN FOR CEILING FINISHES AND I LING HEIGHTS ARE FROM FIN. FLOOR ELEVATION OF SPAC	
10.		TO HAVE RUBBER TREADS AND RISERS.	
11.		NIC WATER ALCOVES GENERAL NOTE: UNLESS NOTED OR D	
		N THREE WALLS OF THE WATER COOLER ALCOVE RECESS, S NOTED OR DETAILED OTHERWISE PROVIDE CERAMIC TILE	
	PROVID	E MARBLE TRANSITION STRIP BETWEEN HARD TILE FLOOR	
12.	PATCH	FLOOR IN THIS AREA TO MATCH EXISTING	
	MATERIAL	_ & FINISH KEY	
	<b>CEILING</b>		FLOORS
	ACT CAT	ACOUSTICAL TILE 2'-0" X 2'-0" COATED ACOUSTICAL TILE 2'-0" X 2'-0"	AS C
	ECC	EXTERIOR COATING ON CONCRETE	CONC
	ECP	EXTERIOR COATING ON PLASTER	CONC-AB
	ES	EXPOSED STRUCTURE, UNPAINTED	CONC-ST
	PES ESP	EXPOSED STRUCTURE, PREFINISHED EXPOSED STRUCTURE, PAINT SEMI-GLOSS	CT-B CT-T
	EFTR	EXISTING FINISH TO REMAIN. APPLY MATCHING NEW FINISH	EFTR
		TO NEW WORK AND REPAIR ANY DAMAGED FINISH TO MATCH EXISTING.	
	EXIST.	EXISTING	EPOXY
	FRA	FIRE RATED ASSEMBLY	EXIST.
	FRP GB	FIBBER REINFORCED PLASTIC PANEL GYPSUM BOARD-UNPAINTED	FARF GC
	GLP	GYPSUM LAY-IN PANEL	GWF
	MP	METAL PREFINISHED PANEL	LIN.
	PAT PC	PATTERNED ACOUSTICAL TILE 2'-0" X 2'-0" GRID PAINTED CONCRETE	M PCT
	PGB	PAINTED CONCRETE PAINTED GYPSUM BOARD - SEMI-GLOSS	PWD
	PP	PAINTED PLASTER	QT
	PSC	PLASTER, SPECIAL COATING	QT-B
	SYNSTUC. TAT	SYNTHETIC STUCCO TEGULAR ACOUSTICAL TILE 2'-0" X 2'-0"	SF SWF
	VFI	VINYL FACE INSULATION	SV
	-	NONE, NO WORK REQUIRED	TERZ
	TCT	TECTUM CEILING TILE 2'-0" X 2'-0"	Π
	WALLS		WD LVT
	BRICK	NOM.4" FACE BRICK VENEER	-
	CB	CONCRETE BLOCK - UNPAINTED	BASE
	CT-B	4"X4" CERAMIC TILE IN SETTING BED	CT
	CT-T ECC	4"X4" CERAMIC TILE, THIN-SET EXTERIOR COATING ON CONCRETE	EFTR
	ECP	EXTERIOR COATING ON PLASTER	
	EFTR	EXISTING FINISH TO REMAIN. APPLY MATCHING NEW	EPOXY
		FINISH TO NEW WORK AND REPAIR ANY DAMAGED FINISH TO MATCH EXISTING.	EXIST.
	EPCB	EPOXY PAINTED CONCRETE BLOCK	LIN.
	EPGB	EPOXY PAINTED GYP. BD.	PCT
	EXIST.	EXISTING	PW OT B
	GB LECB	GYPSUM BOARD - UNPAINTED INDUSTRIAL LATEX ENAMEL PAINTED CONC BLK	QT-B R
	LECB LECB-FG	INDUSTRIAL LATEX ENAMEL PAINTED CONC BLK INDUSTRIAL LATEX ENAMEL PAINTED CONC BLK,	SF
		FOOD GRADE	Т
	LEGB	INDUSTRIAL LATEX ENAMEL PAINTED GYP BD	-
	M PCB	MARBLE PAINTED CONCRETE BLOCK - SEMI-GLOSS	
	PCB-A	PAINTED CONCRETE BLOCK - ACRYLIC	
	PCONC	PAINTED CONCRETE - SEMI-GLOSS ENAMEL	
	PGB PGB A	PAINTED GYPSUM BOARD, SEMI-GLOSS	
	PGB-A PLS	PAINTED GYPSUM BOARD - ACRYLIC PLASTIC LAMINATE	
	PP	PAINTED PLASTER	
	UPCB		
	WC VCCB	VINYL WALL COVERING, FIELD APPLIED	
	VCGB WC	VINYL COVERED GYPSUM BOARD, PREFINISHED WALL CARPETING	
	WP	WOOD PANELING	
	-	NONE, NO WORK REQUIRED	

IS SPACE. RING SELECTED FROM

THIS SPACE.

#### I THIS AREA.

ESCRIBE UNLESS OTHERWISE NOTED. OTHERWISE PROVIDE CERAMIC TILES TILE TO BE FULL HEIGHT OF WALLS, NG (CT-) AND SETTING BED AR FLOOR, ADJACENT FINISHED FLOOR.

# ATHLETIC SURFACE

CARPET - PVC BACKED CONCRETE, SEALED

CONCRETE WITH ABRASIVE FIN. (SEALED) CONCRETE - STAINED

2"X2" CERAMIC TILE IN SETTING BED 2"X2" CERAMIC TILE, THIN-SET

EXISTING FINISH TO REMAIN. AND REPAIR ANY DAMAGED FINISH

TO MATCH EXISTING.

EPOXY FLOORING SYSTEM EXISTING

FLUID APPLIED RESILIENT FLOORING GYM CARPET

GYM WOOD FLOOR LINOLEUM

MARBLE

PRE-CAST TERRAZZO PAINTED PLYWOOD FLOOR

QUARRY TILE QUARRY TILE FLOOR ON SETTING BED

SEAMLESS FLOORING STAGE WOOD FLOOR

SHEET VINYL MONOLITHIC TERRAZZO

TERRAZZO TILE

WOOD VINYL COMPOSITION TILE

NONE, NO WORK REQUIRED

CERAMIC TILE EXISTING FINISH TO REMAIN. APPLY MATCHING NEW FINISH TO NEW WORK AND REPAIR ANY DAMAGED FINISH TO MATCH EXISTING. EPOXY FLOORING SYSTEM EXISTING LINOLEUM PRE-CAST TERRAZZO

PAINTED WOOD QUARRY TILE ON SETTING BED

RUBBER SEAMLESS BASE

TERRAZZO AND SETTING BED NONE, NO WORK REQUIRED

## GENERAL NOTES

DOOR FRAMES TO HAVE EQUAL RABBETS.

WHERE GYPSUM BOARD IS APPLIED TO THE FACE OF CONCRETE BLOCK WALLS, ADJUST DEPTH OF 2. FRAME TO ACCOMODATE THE GYPSUM BOARD AND FURRING SO THAT THE FRAME FULLY WRAPS AROUND BOTH THE BLOCK AND THE GYPSUM BOARD.

UNLESS NOTED OTHERWISE, DOORS TO BE UNDERCUT 3/4".

### DOOR SCHEDULE REMARKS

DOOR AND FRAME TO BE INSTALLED IN A MANNER TO RESIST PASSAGE OF SMOKE. 1

2. DOOR FRAME TO SET 1'-0" ABOVE FINISH FLOOR.

PROVIDE DOUBLE EGRESS FRAME. 3

- DOORS EQUIPPED WITH ELECTROMAGNETIC HOLD OPEN DEVICES & SMOKE DETECTORS (TWO 4.
- EACH), CONNECTED TO AND ACTIVATED BY THE BUILDING FIRE ALARM SYSTEM. 5. CASED OPENING FRAME: PROVIDE A CASED OPENING FRAME. FRAME TO HAVE A PROFILE TO
- MATCH STANDARD DOOR FRAMES.
- 6. DOOR FRAME IS NOT TO INTERFERE WITH PROPER RUNNING CLEARANCES OF ELEVATOR
- SELF CLOSING SELF LOCKING FIRE RATED DOOR 7.
- 8. EXISTING DOOR TO REMAIN REPAIR BROKEN NARROW LITE IN DOOR
- 9. REPLACE EXISTING DOOR AND CENTER MULLION; EXISTING FRAME TO REMAIN

#### DOOR TYPE NOTES

- REFER TO SCHEDULE FOR LOCATION OF EACH DOOR TYPE. NOT ALL DOOR TYPES NECESSARILY USED. 1. 2. FOR DOOR SIZE REFER TO SCHEDULE
- 3.
- HOLLOW MTL. & WOOD DOORS W/GLASS TO HAVE MTL. GLASS KITS. REFER TO DETAIL # 5/A3.2. 4. AT LOUVERED DOORS PROVIDE FIBERGLASS INSECT SCREEN ON INSIDE OF DOOR. SCREEN TO BE 16 MESH/INCH.
- DOOR AND HARDWARE MANUFACTURERS SHALL COORDINATE THE LOCATION OF HORIZONTAL 5. RAILS ON FULL GLASS AND FULL LOUVERED DOORS WITH LOCATION OF PANIC DEVICES AND LOCKSETS. THE PANIC DEVICE AND LOCKSET SHALL BE CENTERED ON THE HORIZONTAL RAIL. NO PORTION OF THE HARDWARE SHALL EXTEND OVER THE GLASS OR GLASS LIGHT KIT.

# GLASS TYPE NOTES - DOORS, TRANSOMS, SIDELIGHTS & **VIEW WINDOWS**

- 1. PROVIDE GLASS IN DOORS, TRANSOMS, SIDELIGHTS & VIEW WINDOWS WHERE THEY OCCUR. a. WHERE DOORS ARE ADJACENT TO VIEW WINDOWS, GLASS IN DOOR TO MATCH GLASS IN ADJACENT WINDOWS.
- 2. GLASS IN INTERIOR DOORS, TRANSOMS, SIDE LIGHTS AND VIEW WINDOWS TO BE:
- a. NON RATED WALLS (INCLUDING WALLS DESIGNATED AS "D' & "T"): 1/4" CLEAR TEMPERED GLASS
- b. FIRE RATED WALLS (1 AND 2 HOUR WALLS): IN FIRE AND SMOKE RATED (TYPE "S" AND "S1") WALLS GLASS TO BE 1/4" CLEAR TEMPERED WIRE-LESS GLASS.
- 3. GLASS IN EXTERIOR DOORS, TRANSOMS, SIDELIGHTS AND WINDOWS TO BE:
  - a. EXTERIOR DOORS: 5/8" INSULATED, TEMPERED, TINTED.
  - b. EXTERIOR TRANSOMS & SIDELIGHTS: 1" INSULATED, TEMPERED, TINTED.
  - c. EXTERIOR WINDOWS: 1" INSULATED, TINTED.
- 4. INSTALL GLASS IN HOLLOW METAL FRAME IN ACCORDANCE WITH DETAIL # 5/A3.2.

